

Performance Data for the AquaSana Drinking Water Filter Models AQ-4000/4600/4601

Replacement	Operating pressure range	Rated capacity	Operating temp range	Rated flow
AQ-4035	20-80 psi (1.40-5.624 kg/cm ²)	450 gallons	40-90° F (4.44-32.2° C)	0.5 gpm

Manufactured by: AquaSana, Inc. 6310 Midway Road · Haltom City, Texas 76117 · 866.662.6885

Testing Performed under NSF/ANSI Standards 42 and 53 and in accordance with the California Department of Health Services Drinking Water Treatment Device Program. This system has been tested according to NSF/ANSI 42, 53 & 401 for reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 42, 53 & 401.

NSF/ANSI 42	Influent Challenge Concentration	Reduction requirement	Overall % Reduction	Results
Chlorine Reduction, Free Available	2.0 ± 10% mg/L	50%	>97.4%	Pass
Chloramine Reduction, Free Available	3.0 ± 10% mg/L	5 mg/L	>97.4%	Pass
Particulate Reduction Class I (0.5 µ to <1 µ)	at least 10,000 particles/mL	85%	>99.9%	Pass

NSF/ANSI 53	Influent Challenge Concentration	Reduction requirement	Overall % Reduction	Results
Cyst Live Cryptosporidium & Giardia	min 50,000/L	99.95%	>99.99%	Pass
Mercury Reduction pH 8.5	0.006 ± 10% mg/L	<2 ug/L	>95.8%	Pass
Mercury Reduction pH 6.5	0.006 ± 10% mg/L	<2 ug/L	>96.5%	Pass
Lead Reduction pH 6.5	.15 ± 10% mg/L	<10 ug/L	>99.3%	Pass
Lead Reduction pH 8.5	.15 ± 10% mg/L	<10 ug/L	>99.3%	Pass
MTBE Reduction	.15 ± 20% mg/L	<5 ug/L	86.6%	Pass
Turbidity	11 ± 1 NTU	<0.5 NTU	99.0%	Pass
VOC Surrogate Test	300 ± 30 µg/L	95%	99.4%	Pass
Asbestos Reduction	107 to 108 fibers/L; fibers greater than 10 µm in length	99%	>99%	Pass

NSF/ANSI 401	Maximum Concentration	Minimum Reduction	Overall % Reduction	Results
Phenytoln	30 ng/L	95.50%	95.6%	Pass
Ibuprofen	60 ng/L	95.3%	95.4%	Pass
Naproxen	20 ng/L	96.3%	96.4%	Pass
Estrone	20 ng/L	96.30%	96.5%	Pass
Bisphenol A	300 ng/L	98.80%	98.9%	Pass
Nonyl phenol	200 ng/L	97.50%	97.5%	Pass

Organic chemicals included by surrogate testing				
VOCs (by surrogate testing using chloroform)	Drinking water regulatory level (MCL/MAC) mg/L	Influent/Unfiltered	Effluent/Filtered	Percent Reduction
alachlor	0.002	0.050	0.001	>98%
atrazine	0.003	0.100	0.003	>97%
benzene	0.005	0.081	0.001	>99%
carbofuran	0.04	0.190	0.001	>99%
carbon tetrachloride	0.005	0.078	0.0018	98%
chlorobenzene	0.1	0.077	0.001	>99%
chloropicrin	—	0.015	0.0002	99%
2,4-D	0.07	0.110	0.0017	98%
dibromochloropropane (DBCP)	0.0002	0.052	0.00002	>99%
o-dichlorobenzene	0.6	0.080	0.001	>99%
p-dichlorobenzene	0.075	0.040	0.001	>98%
1,2-dichloroethane	0.005	0.088	0.0048	95%
1,1-dichloroethylene	0.007	0.083	0.001	>99%
cis-1,2-dichloroethylene	0.07	0.170	0.0005	>99%
trans-1,2-dichloroethylene	0.1	0.086	0.001	>99%
1,2-dichloropropane	0.005	0.080	0.001	>99%
cis-1,3-dichloropropylene	—	0.079	0.001	>99%
dinoseb	0.007	0.170	0.0002	99%
endrin	0.002	0.053	0.00059	99%
ethylbenzene	0.7	0.088	0.001	>99%
ethylene dibromide (EDB)	0.00005	0.044	0.00002	>99%
haloacetonitriles (HAN)				
bromochloroacetonitrile	—	0.022	0.0005	98%
Dibromoacetonitrile	—	0.024	0.0006	98%
Dichloroacetonitrile	—	0.0096	0.0002	98%
Trichloroacetonitrile	—	0.015	0.0003	98%
haloketones (HK)				
1,1-dichloro-2-propanone	—	0.0072	0.0001	99%
1,1,1-trichloro-2-propanone	—	0.0082	0.0003	96%
heptachlor (H-34, Heptox)	0.0004	0.025	0.00001	>99%
heptachlor epoxide	0.0002	0.0107	0.0002	98%
hexachlorobutadiene	—	0.044	0.001	>98%
hexachlorocyclopentadiene	0.05	0.060	0.000002	>99%
lindane	0.0002	0.055	0.00001	>99%
methoxychlor	0.04	0.050	0.0001	>99%
pentachlorophenol	0.001	0.096	0.001	>99%
simazine	0.004	0.120	0.004	>97%
styrene	0.1	0.150	0.0005	>99%
1,1,2,2-tetrachloroethane	—	0.081	0.001	>99%
tetrachloroethylene	0.005	0.081	0.001	>99%
toluene	1	0.078	0.001	>99%
2,4,5-TP (silvex)	0.05	0.270	0.0016	99%
tribromoacetic acid	—	0.042	0.001	>98%
1,2,4-trichlorobenzene	0.07	0.160	0.0005	>99%
1,1,1-trichloroethane	0.2	0.084	0.0046	95%
1,1,2-trichloroethane	0.005	0.150	0.0005	>99%
trichloroethylene	0.005	0.180	0.0010	>99%
Trihalomethanes (THMs)				
Bromodichloromethane (THM)				
Bromoform (THM)	0.080	0.300	0.015	95%
Chloroform (THM)				
Chlorodibromomethane (THM)				
Xylenes (total)	10	0.070	0.001	>99%



System tested and certified by NSF International against NSF/ANSI Standard 42, 53 and 401 for the reduction of the claims specified on the Performance Data Sheet and at www.nsf.org.



Filter is only to be used with cold water.



Filter usage must comply with all state and local laws.



Testing was performed under standard laboratory conditions, actual performance may vary.



Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.



See owner's manual for general installation conditions and needs plus manufacturer's limited warranty.

• All contaminants reduced by this filter are listed.

• Not all contaminants listed may be present in your water.

• Filter does not remove all contaminants that may be present in tap water.



Do not use with water that is microbiologically unsafe or of unknown water quality without adequate disinfection before or after the system.